

## SHORE POWER CORDSETS

- Watertight plug assembly for safety & overall durability
- Corrosion resistant nickel-plated brass connectors
- Standard threaded ring on each end creates watertight seal between the adapter & inlet
- Power Indicator Red LED for easy identification
- Heavy-duty, super flexible marine-grade 10/3 STW cable (30A models)
- Heavy-duty, super flexible marine-grade 6/4 STW cable (50A models)
- ETL Listed; CSA Certified



ORDER NO.	Mfr. No.	Replaces	Length	Mechanical Spec:	Strand Count	Amps	Rated
<b>015-AC12340</b>	AC12340	199116	12'	NEMA L5-30P Male Plug to NEMA L5-30R Female twist lock	41	30A	125VAC
<b>015-AC12350</b>	AC12350	199117	25'	NEMA L5-30P Male Plug to NEMA L5-30R Female twist lock	41	30A	125VAC
<b>015-AC12360</b>	AC12360	199120	50'	NEMA L5-30P Male Plug to NEMA L5-30R Female twist lock	41	30A	125VAC
<b>015-AC12370</b>	AC12370	6152SPP-25	25'	NEMA SS2-50P Male Plug to NEMA SS2-50R Female twist lock	104	50A	125/250VAC
<b>015-AC12380</b>	AC12380	6152SPP	50'	NEMA SS2-50P Male Plug to NEMA SS2-50R Female twist lock	104	50A	125/250VAC

### Y ADAPTER - 50A 125/250V (SS2-50P) MALE TO (2) 30A 125V FEMALE (L5-30R)

- 50A 125/250V Male Locking to (2) 30A 125V Female Locking Adapters
- Max Amp: 50A
- Max Voltage: 250VAC
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass
- Molded Plugs: Nylon
- Mechanical Spec: SS2-50P Male to (2) L5-30
- ETL Listed



**ORDER NO. 015-AC12430** Mfr. No. AC12430

### Y ADAPTER - 50A 125/250V (SS2-50R) FEMALE TO (2) 30A 125V (L5-30P) MALE SHORE POWER REVERSE "Y" ADAPTER

- (2) 30A 125V (L5-30P) Male Locking (L5-30P) to 50A 125V Female Locking Adapters
- Max Amp: 30A
- Max Voltage: 250VAC
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass
- Molded Plugs: Nylon
- Mechanical Spec: (2) L5-30P Male to L5-30R Female Twist-Lock



**ORDER NO. 015-AC12450** Mfr. No. AC12450

### Y ADAPTER - 30A 125V (L5-30P) MALE TO (2) 30A 125V (L5-30R) FEMALE

- 30A 125V Male Locking to (2) 30A 125V Female Locking Adapters
- Max Amp: 30A
- Max Voltage: 125VAC
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass
- Molded Plugs: Nylon
- Mechanical Spec: L5-30P Male to (2) L5-30R Female Twist-Lock
- CSA Listed



**ORDER NO. 015-AC12460** Mfr. No. AC12460

### 15A AC INLET

- 30A, 125VAC rated
- 3-Wire locking design
- Corrosion & UV resistant design
- Convenient sealing cap stays in open position without holding in place
- Rear enclosure keep electrical components covered for maximum safety
- Elegant, premium designed sealing cover
- Easy to install or retrofit older inlets
- UL Listed, CSA Listed



**ORDER NO. 015-AC12540** Mfr. No. AC12540

### 30A 125V SQUARE WHITE INLET

- 30A, 125VAC rated
- 3-Wire locking design
- Corrosion & UV resistant design
- Convenient sealing cap stays in open position without holding in place
- Rear enclosure keep electrical components covered for maximum safety
- Elegant, premium designed sealing cover
- Easy to install or retrofit older inlets
- UL Listed, CSA Listed



**ORDER NO. 015-AC12520** Mfr. No. AC12520

# SIERRA<sup>®</sup>

**SPECIAL BOOKING PRICING  
AVAILABLE UNTIL FEB 29, 2024**

## PIGTAIL ADAPTER - 30A 125V (L5-30P) MALE TO 50A 125/250V (SSR-50R) FEMALE

- Used to connect a 30A 125VAC Male Dockside Connector to a 50A 125/250VAC Female Boatside Inlet
- Max Amp: 30A
- Max Voltage: 125VAC
- Cable Size: 10 AWG
- Conductors: 3
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass
- Molded Plugs: Nylon
- Mechanical Spec: L5-30P Male to SS2-50R Female Twist-Lock
- CSA Listed



**ORDER NO. 015-AC12500** Mfr. No. AC12500

## PIGTAIL ADAPTER - 50A 125V/250V (SS2-50P) MALE TO 30A 125V (L5-30R) FEMALE

- Used to connect a 50A 125/250VAC Male Dockside Connector to a 30A 125V Female Boatside Inlet
- Max Amp: 30A
- Max Voltage: 250VAC
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass
- Molded Plugs: Nylon
- Mechanical Spec: SS2-50P Male to L5-30R Female Twist-Lock
- CSA Listed



**ORDER NO. 015-AC12440** Mfr. No. AC12440

## PIGTAIL ADAPTER - 30A 125V (L5-30P) MALE TO 15A 125V (5-15R) FEMALE

- Used to connect a 30A 125VAC Male Dockside Connector to a 15A 125VAC Boatside Female Inlet
- Max Amp: 15A
- Max Voltage: 125VAC
- Cable Size: 10 AWG
- Conductors: 3
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass / • Molded Plugs: Nylon
- Mechanical Spec: 5-15P Male to L5-30R Female Twist-Lock
- CSA Listed



**ORDER NO. 015-AC12510** Mfr. No. AC12510

## PIGTAIL ADAPTER - 15A 125V (5-15P) MALE STRAIGHT BLADE TO 30A 125V (L5-30R) FEMALE LOCKING

- Used to connect a 15A 125VAC Male Straight Blade Dockside Connector to a 30A 125VAC Female Locking Boatside Inlet
- Max Amp: 15A
- Max Voltage: 125VAC
- Cable Size: 10 AWG
- Conductors: 3
- Jacket: PVC
- Jacket Rating: STW 600VAC @ 60°C
- Contacts: Nickel-Plated Brass / • Molded Plugs: Nylon
- Mechanical Spec: 5-15P Male to L5-30R Female Twist-Lock
- CSA Listed



**ORDER NO. 015-AC12480** Mfr. No. AC12480

## FEMALE CONNECTOR - 30A 125V (L5-30R)

- 30A, 125VAC rated
- NEMA L5-30R configuration
- Marine-grade, heavy-duty construction
- Ribbed outer casing for superior grip
- Water-proof seal keeps out moisture & contaminants
- Strain relief secures cord in place with stainless steel hardware
- UL Listed, CSA Listed



**ORDER NO. 015-AC12490** Mfr. No. AC12490

## FEMALE CONNECTOR - 50A 125/250V (SS2-50R)

- 50A, 125VAC rated
- NEMA SS-2 configuration
- Marine-grade, heavy-duty construction
- Ribbed outer casing for superior grip
- Water-proof seal keeps out moisture & contaminants
- Strain relief secures cord in place with stainless steel hardware
- UL Listed, CSA Listed



**ORDER NO. 015-AC12470** Mfr. No. AC12470

## AC INLET W/ 16" EXTENSION CORD

- Use as a pass-thru 15A 125VAC connection
- Press-fit, watertight rubber cap & rubber gasket protects from water intrusion
- Heavy-duty wire
- Simple installation requiring only a 2" hole size & a phillips screw driver
- Conductor Size: 14 AWG
- Conductors: 3
- Input: 5-15P
- Output: 5-15R
- Cord Length: 16"
- Max Amperage: 15A
- Max Voltage: 125VAC
- ETL Listed



**ORDER NO. 015-AC12390**  
Mfr. No. AC12390

## AC INLET W/ 6' EXTENSION CORD

- Use as a pass-thru 15A 125VAC connection
- Press-fit, watertight rubber cap & rubber gasket protects from water intrusion
- Heavy-duty wire
- Simple installation requiring only a 2" hole size & a phillips screw driver
- Conductor Size: 14 AWG
- Conductors: 3
- Input: 5-15P
- Output: 5-15R
- Cord Length: 6'
- Max Amperage: 15A
- Max Voltage: 125VAC
- ETL Listed



**ORDER NO. 015-AC12400**  
Mfr. No. AC12400

## AC INLET W/ 12' EXTENSION CORD

- Use as a pass-thru 15A 125VAC connection
- Press-fit, watertight rubber cap & rubber gasket protects from water intrusion
- Heavy-duty wire
- Simple installation requiring only a 2" hole size & a phillips screw driver
- Conductor Size: 14 AWG
- Conductors: 3
- Input: 5-15P
- Output: 5-15R
- Cord Length: 12'
- Max Amperage: 15A
- Max Voltage: 125VAC
- ETL Listed



**ORDER NO. 015-AC12410**  
Mfr. No. AC12410

## AC INLET W/ TWIN 18" EXTENSION CORD

- Use as a pass-thru 15A 125VAC connection to twin AC out cables
- Press-fit, watertight rubber cap & rubber gasket protects from water intrusion J47
- Heavy-duty wire
- Simple installation requiring only a 2" hole size & a phillips screw driver
- Conductor Size: 14 AWG
- Conductors: 3
- Input: 5-15P
- Output: 5-15R
- Cord Length: 18" / Cords: 2
- Max Amperage: 15A
- Max Voltage: 125VAC
- ETL Listed



**ORDER NO. 015-AC12420**  
Mfr. No. AC12420